



## HD 13/35-4 Cage

This product uses up to 350 bar of pressure to remove even the most stubborn dirt. The robust cage design provides all-round protection and enables safe crane loading. With sack-trolley principle for easy transportation.



### 1 High-performance crankshaft pump

- Reliable and durable Kärcher high-performance crankshaft pump ensures optimal pressure.

### 2 Safe storage

- Accessories and tools are stored in a protected compartment. This means that everything is always in its place.



## HD 13/35-4 Cage

- Robust industrial gun
- Dry run protection (optional)

### Technical data

<b>Order no.</b>	1.367-154.0	
<b>EAN code</b>	4039784730984	
<b>Working pressure</b>	<b>bar / MPa</b>	100-350 / 10-35
<b>Flow rate</b>	<b>l/h</b>	500-1300
<b>Inlet temperature</b>	<b>°C</b>	max. 60
<b>Drive</b>	E-Motor 400 V / 50 Hz	
<b>Fuel</b>	electric	
<b>Pump type</b>	Maximum performance Kärcher crankshaft pump	
<b>Motor rating</b>	<b>kW</b>	15
<b>Weight without accessories</b>	<b>kg</b>	160
<b>Weight (with accessories)</b>	<b>kg</b>	190
<b>Dimensions (L × W × H)</b>	<b>mm</b>	930 × 800 × 920

### Equipment

<b>Electro start</b>	-	
<b>High-pressure hose</b>	<b>m</b>	10 / Heavy duty
<b>Spray gun</b>	Industrial trigger gun	
<b>Stainless steel lance</b>	<b>mm</b>	700
<b>Flat jet nozzle</b>	■	
<b>Safety valve</b>	■	
<b>Elapsed time counter</b>	■	

■ Included in the scope of supply.

# HD 13/35-4 CAGE

## 1.367-154.0

**KÄRCHER**



		Order no.	Length				Price	Description	
<b>High-pressure hoses</b>									
Pressure hose	1	6.391-846.0						650 bar, M 22 x 1.5	■
	2	6.391-856.0						650 bar, M 22 x 1.5.	□
	3	6.391-848.0						650 bar, M 22 x 1.5	□
	4	6.391-857.0						650 bar, M 22 x 1.5.	□
	5	6.391-847.0							□
	6	6.391-019.0						Durable, abrasion-resistant and flexible multi-layer steel-reinforced hose with connection size M 22 x 1.5. Suitable for up to 620 bar working pressure.	□
<b>Trigger guns</b>									
Kärcher industry gun	7	4.775-824.0						650 bar - industrial spray gun with optimised flow. Robustness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	■
<b>Spray lances</b>									
Spray lance	8	4.760-679.0						With nozzle holder.	■
	9	4.760-653.0							□
Jet pipe complete 1550 mm 65 MPa	10	4.760-675.3							□
Spray lance	11	4.760-677.0							□
Spray lance extension	12	4.760-699.0						Spray lance extension 800 mm, 65 MPa.	□
<b>Power nozzles</b>									
Flat jet nozzle	13	5.765-166.0						15° flat jet nozzle 15049 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h (electr.).	■
Point jet nozzle	14	5.765-162.0						Point jet nozzle 0049 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h. (electr.).	□
<b>Attachment kits</b>									
ABS protection against dry run	15	2.641-922.0						For electric motors.	□
ABS protection against water shortage	16	2.851-028.0						ABS steering rollers.	□
<b>Kupplungen und Verbinder</b>									
Coupling	17	4.403-004.0						For joining and extending HD hoses. Connection 2 x M 22 x 1.5. Material: Stainless steel.	□
Grease for stainless steel threaded joints	18	6.280-180.0						Grease for stainless steel screw connections.	□
<b>Single-jet rotary nozzles</b>									
Rotary jet	19	4.767-173.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, brass.	□
Power rotary jet F7	20	6.415-914.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, stainless steel.	□
Power rotary jet repair kit F7	21	6.025-436.0						Repair kit for power rotary jet, order no. 6.415-914.0. Suitable for 350 bar working pressure and 1,300 l/h water flow rate. Includes rotor, seat and O-ring (28 x 2).	□
Tool for changing rotor seat	22	6.025-233.0						For F3, F4, F1, F25.	□
Power rotary jet F7	23	6.415-085.0						350 bar, 1.35 mm, 1,300 l/h, M 20 x 1, stainless steel.	□
<b>Screw nozzles F21</b>									
Dummy nozzle F21	24	6.025-237.0						F21 screw-on dummy nozzle. Suitable for working pressures of up to 3,000 bar.	□
Round jet nozzle F21, Saphir	25	9.886-216.0						Screw-on F21 sapphire round jet nozzle with a diameter of 0.90 mm. Suitable for working pressures of up to 3,000 bar.	□

■ Included in the scope of supply. □ Available accessories.

# HD 13/35-4 CAGE

## 1.367-154.0

**KÄRCHER**



MISSING PICTURE:  
M:\print\9899828\_  
std\_1\_86584\_acc.  
tif

		Order no.	Length				Price	Description	
<b>Pipe cleaning</b>									
Foot valve for pipe cleaning	26	6.470-223.0						Foot valve for convenient and safe use of accessories for effective pipe cleaning.	<input type="checkbox"/>
Pipe cleaning nozzle, standard	27	5.763-090.0						Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning nozzle standard 050 50MPa	28	4.765-012.0							<input type="checkbox"/>
Pipe cleaning nozzle Four 050 50MPa	29	4.765-016.0						For pipe cleaning hoses with G1/4" threaded connection: Quattro pipe cleaning nozzle. Nozzle configuration: 3x backward and 1x forward.	<input type="checkbox"/>
Pipe cleaning nozzle, Rotor	30	5.763-092.0						For pipe cleaning hoses with G1/4" threaded connection: Rotor pipe cleaning nozzle. Nozzle configuration: 3x backward.	<input type="checkbox"/>
Pipe cleaning hose	31	6.392-401.0						Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	<input type="checkbox"/>
	32	6.392-402.0						Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	<input type="checkbox"/>
	33	6.392-403.0						For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	<input type="checkbox"/>
<b>Surface cleaner</b>									
Surface Cleaner FRI 50 Me	34	2.643-577.0						Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	<input type="checkbox"/>
Nozzle package 025 FRI 50 Me	35	6.415-045.0						Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 025.	<input type="checkbox"/>
<b>Abrasive blaster</b>									
Required adapter for abrasive blasters	36	5.401-325.0						M 20 x 1 IG to 9/16" UNF AG.	<input type="checkbox"/>
Abrasive blaster, incl. 3 x 0.7 nozzle	37	9.872-435.0						Abrasive spray head with nozzle size 3 x 0.7 mm for wet sand blasting. Only includes spray head. Without hose and lance.	<input type="checkbox"/>
Replacement nozzle for abrasive blaster	38	6.025-346.0						Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	<input type="checkbox"/>
F98 nozzle kit, D 0.70 mm	39	9.886-551.0						For wet sand blasting: three-nozzle kit for abrasive spray head. Nozzle size 0.7 mm.	<input type="checkbox"/>
F98 nozzle for abrasive blaster	40	6.025-255.0						Nozzle (nozzle size 0.7 mm) for abrasive spray head for wet sand blasting.	<input type="checkbox"/>
Suction lance	41	6.025-258.0						For the suction of spray agents.	<input type="checkbox"/>
Abrasive material hose	42	6.025-308.0						Abrasive hose.	<input type="checkbox"/>
Mounting tool for nozzle set	43	6.025-257.0						For F98 nozzles.	<input type="checkbox"/>
Abrasive	44	6.025-309.0						25 kg, 0.5-1.00 mm, garnet sand.	<input type="checkbox"/>
	45	6.025-310.0						25 kg, 0.7-1.40 mm, garnet sand.	<input type="checkbox"/>
<b>Multi-jet rotary nozzles</b>									
Nozzle body	46	9.917-677.0						Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	<input type="checkbox"/>
Nozzle carrier head TD09	47	9.899-828.0						6-jet nozzle carrier head for F21 nozzle. Suitable for working pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.